

## DECLARATION OF PERFORMANCE NO ESG4LE\18\4\18\ESG4LE+A (SSP U G)



Manufacturer:

1. EFFECTOR S.A.  
ul. Hauke-Bosaka 2  
25-214 Kielce POLSKA

2. EFFECTOR S.A.  
Oddział Wędkowy  
83-115 Swarzędz POLSKA



|                                                                                                                                                                                                                                                                         |  |                                                                                                                                                                       |              |               |                 |             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---------------|-----------------|-------------|
| Harmonised standard:                                                                                                                                                                                                                                                    |  | PN-EN 1279-5:2018 attachment ZA                                                                                                                                       |              |               |                 |             |
| Intended use/es:                                                                                                                                                                                                                                                        |  | Insulated glass unit / for use in construction industry and construction works                                                                                        |              |               |                 |             |
| Unique identification code of the product-type:                                                                                                                                                                                                                         |  | LG04T\Z\H\PSU18SZ\A\FLO4\SU18SZ\A\LG04T\Z\H\PESG CG PREMIUM 4MM ZAT HART\RAMKA SSP 18 SZ ULTI\ARGON\FLOAT 4MM\RAMKA SSP 18 SZ ULTI\ARGON\ESG CG PREMIUM 4MM ZAT HART) |              |               |                 |             |
| Declared performance/s:                                                                                                                                                                                                                                                 |  | Standard                                                                                                                                                              | AVCP Systems | Unit of meas. | Symbol          | Value       |
| Safety in the case of fire – Fire resistance                                                                                                                                                                                                                            |  | EN-13501-2                                                                                                                                                            | 1            | -             |                 | NPD         |
| Safety in the case of fire – Reaction to fire                                                                                                                                                                                                                           |  | EN-13501-1                                                                                                                                                            | 3,4          | -             |                 | NPD         |
| Safety in the case of fire – Impact of external fire                                                                                                                                                                                                                    |  | -                                                                                                                                                                     | 3,4          |               |                 | NPD         |
| Safety of use – Resistance to bullets: behavior in the case of breakdown and resistance to attack                                                                                                                                                                       |  | EN 1063                                                                                                                                                               | 1            | -             |                 | NPD         |
| Safety of use – Resistance to explosion: behavior in the case of breakdown and resistance to attack                                                                                                                                                                     |  | EN 13541                                                                                                                                                              | 1            | -             |                 | NPD         |
| Safety of use – Burglary resistance: behavior in the case of breakdown and resistance to attack                                                                                                                                                                         |  | EN 356                                                                                                                                                                | 3            | -             |                 | NPD-NPD-NPD |
| Safety of use – Resistance to pendulum impact: behavior in the case of breakdown (safe cracking) and impact resistance                                                                                                                                                  |  | EN 12600                                                                                                                                                              | 3            | -             |                 | 1C1-NPD-1C1 |
| Safety of use – Mechanical resistance: Resistance to sudden temperature changes and temperature differences                                                                                                                                                             |  | EN 572                                                                                                                                                                | 4            | °K            |                 | 200-40-200  |
| Safety of use - Mechanical resistance: Glass resistance to wind, snow pressure, permanent and/or applied load                                                                                                                                                           |  | -                                                                                                                                                                     | 4            | MPa           |                 | 120-45-120  |
| Noise protection: Direct airborne sound insulation 3-examination; 4-estimation; 5-extension EN 12758                                                                                                                                                                    |  | EN 12758                                                                                                                                                              | 3            | dB            | Rw(C;Ctr)       | 32(-1;-6)   |
| Energy saving and heat retention – Thermal properties                                                                                                                                                                                                                   |  | EN 673                                                                                                                                                                | 3            | W/(m2·K)      | Ug              | 0,5         |
| Energy saving and heat retention – Radiometric properties: Light transmittance factor                                                                                                                                                                                   |  | EN 410                                                                                                                                                                | 3            | %             | LT,tv           | 73          |
| Energy saving and heat retention - Radiometric properties: External / internal light reflection factors                                                                                                                                                                 |  | EN 410                                                                                                                                                                | 3            | %             | LR, pv/LR', p'v | 17/17       |
| Energy saving and heat retention - Radiometric properties: Direct solar energy transmittance factor                                                                                                                                                                     |  | EN 410                                                                                                                                                                | 3            | %             | TE, te, ET      | 46          |
| Energy saving and heat retention - Radiometric properties: Direct solar energy reflection factor                                                                                                                                                                        |  | EN 410                                                                                                                                                                | 3            | %             | ERe, pe, ER     | 33          |
| Energy saving and heat retention - Radiometric properties: Total solar energy transmittance factor                                                                                                                                                                      |  | EN 410                                                                                                                                                                | 3            | %             | g               | 53          |
| Notified body:                                                                                                                                                                                                                                                          |  | 1487                                                                                                                                                                  |              |               |                 |             |
| The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. |  |                                                                                                                                                                       |              |               |                 |             |
| Signed for and on behalf of the manufacturer by:                                                                                                                                                                                                                        |  | <br>Paweł Obara                                                                    |              | at Kielce     | on              | 30/12/2024  |
| NPD-No performance determined                                                                                                                                                                                                                                           |  |                                                                                                                                                                       |              |               |                 |             |
| If there are two or more values, this means that the first value refers to the first pane, the second value to the second pane, etc.                                                                                                                                    |  |                                                                                                                                                                       |              |               |                 |             |
| Confirmation of the HST-Heat Soak Test, types of spacer bar and IGU with silicone UV in the documents of purchase.                                                                                                                                                      |  |                                                                                                                                                                       |              |               |                 |             |
| Values of factors apply to vertical glazing, without mullions and glass decorations.                                                                                                                                                                                    |  |                                                                                                                                                                       |              |               |                 |             |
| DESCRIPTION: ESG-toughened glass; TVG-semi-toughened glass; Ar-Argon; Kr-Krypton; Emalit-enameled glass; Sitodruk-silk-screen printing; SI-acoustic foil.                                                                                                               |  |                                                                                                                                                                       |              |               |                 |             |